

PORTA A TRE ANTE
Porte in vetroresina per cabine elettriche

PORTA A TRE ANTE h.2175mm.
CODICE PRODOTTO: PT300

Le porte sono realizzate in resina poliester rinforzata con fibra di vetro SMC Colore grigio ENEL, autoestinguente, secondo le prescrizioni ENEL DS 4974. Hanno un grado di protezione IP 33 secondo la norma CEI-EN 60529, e IK10 secondo CEI-EN 50102. Sono realizzate secondo la specifica tecnica ENEL DS1511. Predisposte per il montaggio di serrature tipo ENEL DS988 con chiusura su tre punti. Per il fissaggio alla parete, il telaio è dotato di otto piastrelle per tasselli od apposite zanche.

THREE DOORS MODEL
Fiberglass doors for electrical cabins

THREE PANELS DOOR h.2175mm
PRODUCT CODE: PT300

The doors are made of reinforced polyester resin with typical ENEL grey SMC fiberglass, self-extinguishing, in compliance with ENEL DS 4974 prescriptions. They have IP33 protection grade included in compliance with standards CEI-EN 60529 and IK10 according to CEI-EN 50102. Made in compliance with ENEL's technical specification DS1511. Prearranged for assembly of ENEL DS988 type locks with locking in three points. For wall hanging, the frame is supplied with eight plates for inserts and special brackets.

DATI TECNICI / TECHNICAL DATA

	base/width	altez./height	prof./depth
10300-00	1813	x 2175	x 45
Dimensioni esterne / External dimensions	1785	x 2145	
Intonaco finito / Finished coating			
Dimensioni utili ingresso due ante Two panels door true dimensions	1111	x 2095	
Dimensioni utili ingresso tre ante Three panels door true dimensions	1700	x 2095	
Apertura / Opening	110°		
Passaggio aria (cmq) / air inlet	480		

