

PORTA AD UN'ANTA

Porte in vetroresina per cabine elettriche

PORTA AD UN'ANTA h.2175mm.

Le porte sono realizzate in resina poliester rinforzata con fibra di vetro SMC Colore grigio ENEL, autoestinguento, secondo le prescrizioni ENEL DS 4974.

Hanno un grado di protezione IP 33 secondo la norma CEI-EN 60529 ed IK10 secondo CEI-EN 50102.

Sono realizzate secondo la specifica tecnica ENEL DS1511.

Predisposte per il montaggio di serrature tipo ENEL DS988 con tre punti di chiusura.

Per il fissaggio alla parete, il telaio è dotato di sei piastrelle per tasselli od apposite zanche.

SINGLE PANEL DOOR

Fibreglas doors for electrical cabins

SINGLE PANEL DOOR h.2175mm

The doors are made of reinforced polyester resin with typical ENEL grey SMC fiberglass, self-extinguishing, in compliance with ENEL DS 4974 prescriptions. They have IP33 protection grade included in compliance with standards CEI-EN 60529 and IK10 according to CEI-EN 50102. Made in compliance with ENEL's technical specification DS1511.

Prearranged for assembly of ENEL DS988 type locks with locking in three points. For wall hanging, the frame is supplied with six plates for inserts and special brackets.

DATI TECNICI / TECHNICAL DATA

10100-00

Dimensioni esterne / External dimensions

Intonaco finito / Finished coating

Dimensioni utili / true dimensions

Apertura / Opening

Passaggio aria (cmq) / air inlet 160

base/width

640 x

altez./height

2175 x 45

614 x

2145

542 x

2095

110°

